LCS-8034TBR4

10 Mbit/s PCI Networkcard
1 x Port RJ-45
1 x Port BNC

10Mbit/s PCI Networkcard with BNC, RJ-45 connectos and optional AUI.

Features:

- Unsurpassed Performance by APX and full-duplex, PCI 32-Bit data bus design
- Full-Duplex allows 20 Mbps effective Bandwidth
- Plug & Play (PnP) for all PnP Platforms
- Auto-sensing BNC & TP ports plus unique optional AUI port
- 32-bit PCI data bus for speed performance
- STP connector – minimizes radial emission and ensures transmission reliability
- 10Base-2 segment up to 300m
- Complete diagnostic program
- Energy saving green Ethernet

Specifications:

Chipset:	Realtek 8029
Standard:	Ethernet IEEE 802.3 CSMA/CD, 10 Mbps
Interfaces:	RJ-45, BNC, and optional AUI
Bus Interface:	32-bit PCI 2+
Voll-Duplex:	up to 20 Mbps
IRQ Line:	auto select
I/O Adresses:	auto select
Boot ROM:	Socket for optional 32 KB PROM, such as NetWare or NT boot PROM
LED:	Link (green) and Activity (red)
Driver:	NetWare, LAN Manager, Windows 95/98, Windows NT, Windows 2000/XP, WfW, PC/TCP, SCO Unix, Lantastic, OS/2 and more
Dimensions:	14,3 X 5,4 cm
Temperature:	0° to 55° C (operating)
Humidity:	10% to 90%
Certificate:	FCC Class A, CE, Novell Approved
Box contains:	PCI-Karte, Driverfloppy, T-connector, Manual
EAN:	4016621000240